

# DSS Double fastening clamp

CE

## Areas of application:

For the parallel laying of two pipes or tubes with no wall distance.

## Installation guide:

- Drill a 6mm Ø hole
- Insert flexible or rigid pipes to the DSS and insert into the drill-hole

## Product details:

Clamping range mm	Type	Content Unit/box	Article number
4–12	DSS 10	200 / 7.200	30220
20–25	DSS 20-25	200 / 4.000	30240
25–32	DSS 25-32	100 / 2.400	30250

## Product benefits/properties:

A drill hole of 6 mm Ø is sufficient for the laying of two pipes.

Drill – insert – that's it.

## Technical data:

Material **halogen-free**, PP, light grey, UV stabilised,  
temperature range: –10 °C to +85 °C,  
silicon-free

Weight per piece\* 0.7 g, 2 g, 2.5 g

\* Listed in product overview order



One borehole is also enough for two pipes – with the double fastening clamp from Schnabl.

Schnabl Stecktechnik GmbH  
Bahnhofplatz 1, 3100 St. Pölten, Austria  
Telephone +43 (0) 2742/221 67-0, Fax +43 (0) 2742/221 67-50  
office@schnabl-steck.at, www.schnabl-steck.at

 **Schnabl**<sup>®</sup>