

EC Euro-Clip

CE

Areas of application:

Used with other Schnabl products, the EC clip can be fixed to concrete, bricks, cable trays, steel, insulation materials, plasterboard and wood with a screw.

- With the ESD Euro-fastening anchor in concrete and brick,
- With the EDV Euro twist-on connection in slotted hole on thin surfaces or cable conduits,
- With the ESV Euro connector lock in round holes on thin surfaces or cable conduits,
- With the DHI fastener for insulation materials,
- With the ESP Euro shooting plate in concrete and steel,
- With the EKP Euro adhesive pad for mounting to all materials
- Or by simply screwing the EC Euro Clip to wood.

Installation guide:

- Even with different pipe diameter dimensions, the EC clamps can be linked together through aligning them on their long sides and then clicking them together.
- If a pipe is mounted at a high temperature or with a heavy weight the usage of the UVB Universal Clamping Bracket should be considered.

Product details:

Insulation pipe Ø	Type	Colour	Content pack/box	Article number
16	EC 16	light grey	100/3.200	31020
20	EC 20	light grey	100/2.400	31080
25	EC 25	light grey	100/2.000	31120
32	EC 32	light grey	50/1.600	31160
40	EC 40	light grey	50/1.100	31200
50	EC 50	light grey	50/700	31220

Other colours on request

Product benefits/properties:

The EC Euro Clip can be positioned by pushing it over the entire clip width (with ESD Euro-fastening anchor, ESP Euro shooting plate, EDV Euro twist-on connection or ESV Euro connector lock) and removed again simply by being snapped off. The functional stacking system means several EC Euro Clips in different sizes can be clipped together.

Technical data:

Material	halogen-free, ABS, light grey, UV stabilised, silicon-free, temperature range: -20 °C to +85 °C
Weight per piece*	3.2 g, 3.6 g, 4.8 g, 6.4 g, 7.8 g, 10.4 g
EAN-Codes halogen-free *	9008439-310203, -310807, -311200, -311606, -312009, -312207

* Listed in product overview order



Together with the UVB Universal clamping bracket, the EC Euro-Clip meets the requirements of a closed clamp so as to prevent slipping when mounting pipes in high ambient temperatures (deformation), for example.



Thanks to the functional clip system, several EC Euro clips can be clipped together in various sizes.