



## RECESSED MCQUEEN



### PRODUCT SPECIFICATION

CODE	TOTAL POWER (W)	LUMENS OUTPUT (lm)	COLOUR TEMPERATURE	EFFICACY (LM/W)	COLOUR
M3R	8	700lm@3K 750lm@4K 720lm@5.7K	3K 4K 5.7K	87-93lm/w	White trim + black housing

### COMMON SPECIFICATION

Power Factor	>0.9	Materials/Construction	Aluminum
Input Voltage	AC200-240V	LED Chip	2835SMD
Beam Angle	90°	Driver Make	Upshine
Glare Rating	>19 (about 30)	Operating Temperature	-20 ~ +45D
Colour Rendering	90	Dimming	Yes
IP Rating	IP44	Projected Life (hrs)	>40,000hrs
Approvals/Certificates	SAA for driver	Class	II
Dimensions	Dia104 x 31mm	Mounting Accessories	No
Other Features	3CCT selectable		

### CERTIFICATES & APPROVALS



Vynco Industries NZ Limited

**Auckland**

P +64 9 525 6051 F +64 9 525 5799

E [vyncoauck@vynco.co.nz](mailto:vyncoauck@vynco.co.nz)

**Christchurch**

P +64 3 379 9283 F +64 3 379 6838

E [chchsales@vynco.co.nz](mailto:chchsales@vynco.co.nz)

[fb/vyncoindustriesltd](https://www.facebook.com/vyncoindustriesltd)

[www.vynco.co.nz](http://www.vynco.co.nz)

## DIMENSIONS

CODE	FASCIA (mm)	HEIGHT (mm)	CUT OUT (mm)
M3R	110Ø	38	90

